

## Outstanding Performance. Amazing Value.

Polk Audio has once again raised the standard for great sounding speakers that also offer incomparable value. The new TSi Series takes entry-level component speaker pricing and gives the audio/home theater buff a lot of Polk Audio for the money. The TSi Series was designed to be highly efficient, so they can be driven easily by unpretentious receivers, and they're voice-matched for lifelike surround sound environments. The new TSi Series' contemporary look was inspired by our top-of-the-line LSi Series and designed to work with today's most stylish televisions and electronic components.

**TSi200****TSi400**

### Floorstanding, Bookshelf And Center Channel Features

- 1" (25mm) silk/polymer composite Dynamic Balance® dome tweeters with powerful neodymium magnet structure delivers clear and detailed high frequency response for realistic reproduction of vocals and instruments.
- Dynamic Balance composite drivers are lightweight and stiff with good damping for high efficiency, excellent bass and lower distortion.
- Multiple small-diameter driver design delivers a more open, "box-less," three-dimensional sound.
- Center channel speakers are magnetically shielded for safe placement near TVs with no risk of video distortion.
- Reversible-design center channel speaker cabinet can be turned upside down to aim "up" when placed under a video monitor.
- Critically tuned flared ports minimize port noise ("chuffing") for good low frequency extension, resulting in natural, full-bodied sound with rich bass.
- Non-resonant all-MDF enclosure construction with 3/4" thick baffles ensures cleaner, clearer, more lifelike sound quality. Tower models feature additional front-to-back and side-to-side internal bracing.
- Computer modeled anti-diffraction grilles.
- Narrow baffle profiles create superior three-dimensional imaging and sound stage.
- High-gloss piano finish on tops, and high gloss piano finish on center channel end caps, complement the latest trends in flat screen TVs.
- Dual 5-way binding post connectors for more secure hook-up options, and bi-wiring and bi-amping flexibility.
- High efficiency design enables the TSi Series to reveal the classic Polk Audio sound (open, spacious and clear) even when driven by modestly-powered amplifiers and receivers.
- Available in two finishes, black & cherry.

**Specifications**

<b>Floorstanding Loudspeakers</b>	<b>TSi500</b>	<b>TSi400</b>	<b>TSi300</b>
Driver Complement	four 6 1/2" (16.5 cm) bilaminate organic fiber drivers, one 1" (2.5 cm) bilaminate silk dome tweeter	three 5 1/4" (13.3 cm) bi-aminated organic fiber drivers, one 1" (2.5 cm) bilaminate silk dome tweeter	two 5 1/4" (13.3 cm) bilaminate organic fiber drivers, one 1" (2.5 cm) bilaminate silk dome tweeter
Frequency Response: Overall / -3 dB Limits	28 Hz - 25 kHz / 38 Hz - 24 kHz	34 Hz - 25 kHz / 44 Hz - 24 kHz	38 Hz - 25 kHz / 47 Hz - 24 kHz
Crossover Frequency	2500 kHz	2500 kHz	2500 kHz
Impedance	8 Ohms	8 Ohms	8 Ohms
Recommended Amplification	20 - 275 Watts / channel	20 - 200 Watts / channel	20 - 150 Watts/channel
Efficiency	91 dB	91 dB	90 dB
Available Finish	black or cherry	black or cherry	black or cherry
Product Weight / Shipping Weight	45 lbs / 50.38 lbs each (20.41 kg / 22.85 kg each)	32lbs / 36.96 lbs each (14.51 kg / 16.76 kg each)	26 lbs / 30.36 lbs each (11.79 kg / 13.77 kg each)
Overall Dimensions	44 3/8" H x 8 1/4" W x 14 3/4" D 112.7 cm H x 20.9 cm W x 37.5 cm D	38 7/8" H x 7" W x 14 1/4" D 98.7 cm H x 17.78 cm W x 36.2 cm D	36 3/8" H x 7" W x 11 1/2" D 92.4 cm H x 17.78 cm W x 29.21 cm D

<b>Bookshelf Loudspeakers</b>	<b>TSi200</b>	<b>TSi100</b>
Driver Complement	two 5 1/4" (13.3 cm) bilaminate organic fiber drivers, one 1" (2.5 cm) bilaminate silk dome tweeter	one 5 1/4" (13.3 cm) bilaminate organic fiber drivers, one 1" (2.5 cm) bilaminate silk dome tweeter
Frequency Response: Overall / -3 dB Limits	43 Hz - 25 kHz / 50 Hz - 24 kHz	53 Hz - 25 kHz / 61 Hz - 24 kHz
Impedance	8 Ohms	8 Ohms
Crossover Frequency	2500 kHz	2500 kHz
Recommended Amplification	20 - 150 Watts / channel	20 - 100 Watts / channel
Efficiency	89 dB	89 dB
Available Finish	black or cherry	black or cherry
Product Weight / Shipping Weight	17 lbs each / 36.3 lbs pair (7.71 kg each / 16.5 kg pair)	10 lbs each / 21.34 lbs pair (4.53 kg each / 9.7 kg pair)
Overall Dimensions	15 7/16" H x 8" W x 11 3/4" D 39.1 cm H x 20.32 cm W x 29.85 cm D	11" H x 7" W x 10 1/4" D 27.94 cm H x 17.78 cm W x 25.90 cm D

<b>Center Channel Loudspeakers</b>	<b>CS20</b>	<b>CS10</b>
Driver Complement	two 6 1/2" (16.5 cm) bilaminate organic fiber drivers, one 1" (2.5 cm) bilaminate silk dome tweeter	two 5 1/2" (13.97 cm) bilaminate organic fiber drivers, one 3/4" (1.9 cm) bilaminate silk dome tweeter
Frequency Response: Overall / -3dB Limits	48 Hz - 25 kHz / 58 Hz - 24 kHz	53 Hz - 25 kHz / 63 Hz - 24 kHz
Impedance	8 Ohms	8 Ohms
Crossover Frequency	2500 kHz	2500 kHz
Recommended Amplification	20 - 150 Watts / channel	20 - 125 Watts / channel
Efficiency	91 dB	91 dB
Magnetic Shielding	yes	yes
Available Finish	black or cherry	black or cherry
Product Weight / Shipping Weight	19 lbs / 22 lbs each (8.61 kg / 9.97 kg pair)	16 lbs / 18.26 lbs each (7.26 kg / 8.28 kg pair)
Dimensions	7 3/8" H x 20" W x 10 3/4" D (18.73 cm H x 50.8 cm W x 27.3 cm D)	6 1/2" H x 20" W x 9 3/4" D (16.5 cm H x 50.8 cm W x 24.77 cm D)

Specifications, dimensions and features subject to change without notice. For more information call us at 1-800-377-7655 (USA and Canada). Outside of North America call +1 (410) 358-3600.