

**You Want Bass That’s Big, Reliable And Easy To Install—Funny, So Do Your Customers**

**Finally An In-Wall That Actually Outperforms Many Free-Standing Powered Subwoofers!**

The CSW155 is for everyone who covets uncompromising bass performance in a nearly invisible package. The CSW155’s single 10" diameter driver is the shallowest ever engineered by Polk, ensuring the CSW155 fits easily in a wall. This is really big bass that’s created with ultra-reliability in mind. A massive 2" Voice Coil for high output and power handling, plus dual spiders that ensure linear excursion and prevent bottoming out are just some of the features that ensure ultimate performance and reliability. A 15 1/2" x 17 1/2" perforated grille that mimics the look of an air register is included with the CSW155. The CSW155 stands 60" tall but fits comfortably between standard 16" on-center studs.



**CSW155 Features**

- **Fits Comfortably** between standard 16" OC (on-center) studs.
- **Single 10" Diameter Driver** is the shallowest driver Polk has ever engineered.
- **Klippel Optimized Woofer**—By using a state-of-the-art Klippel Distortion Analyzer, Polk engineers were able to optimize the woofer’s motor structure, voice coil alignment and suspension for the best possible performance and low distortion even at extreme listening levels.
- **Neodymium Motor Structure**—made the sub’s shallow depth possible without giving up an ounce of performance.
- **Cast Aluminum Basket** is rigid and inert to suppress resonance.
- **Massive 2" Voice Coil** for high bass output and high power handling.
- **Inverted Roll Surround**—highly reliable design maintains its “springiness” over time.
- **Dual Spiders** ensure linear excursion and prevent the driver from bottoming out.
- **Rigid MDF Slot Ported Enclosure**—The port cross section runs the width of the grille. Steel plate on the back of the cabinet stiffens the enclosure for better performance.
- **15 1/2" x 17 1/2" Perforated Aluminum Grille Included.**
- **All Mounting Hardware And Isolation Pads Included.**



**For Optimum Performance, Try This Really Cool Card Trick**

**SWA500 Amp**

The CSW155 is powered by an external 500W Continuous digital amplifier, the SWA500. The bottom line is high power and cool, reliable operation, with precise definition and low distortion.

The SWA500 is supplied with a plugin SPEX Card that pre-programs equalization, infrasonic filter characteristics and power output of the amplifier to optimize its performance for the CSW155.

**Finally, An In-Wall Subwoofer With Better Performance Than Freestanding Models!**

**Specifications**

**CSW155**

Frequency Response	(-3dB) 30-140Hz (36-120Hz)
Impedance	8 Ohms
Driver Diameter	10"
Enclosure Type	Direct Radiating Slot Port
Included Accessories	Grille
Product Weight	36 lbs. (16.33 kgs)
Dimensions	60"L x 14"W x 3 3/8"D
Grille Dimensions	15 1/2" x 17 1/2"
MSRP US\$	\$800

**SWA500**

Power Continuous	500W @ 4 Ohms; 250W @ 8 Ohms
Power Peak	800W @ 4 Ohms
Bandwidth	15Hz-250Hz
Distortion	0.01%
Crossover Freq. Range	40Hz-120Hz
Included Accessories	SPEX Cards; rack ears
Dimensions	17"W x 3 1/2"H x 12 5/8"D
MSRP US\$	\$699.95



CSW155

**The Numbers Don't Lie—The CSW155 Delivers More Deep And Ultra Deep Bass Than Many Freestanding Models!**

	Woofer Size	Power	Ultra Low Bass (20-31.5Hz)	Low Bass (40-63Hz)
CSW155 w/SWA500	10"	250W	103.8dB	120.9dB
Freestanding Subwoofer B	12"	200W	102.9dB	117.0dB
Freestanding Subwoofer C	12"	250W	96.9dB	117.7dB
Freestanding Subwoofer D	12"	300W	95.2dB	116.9dB

Specifications, dimensions and features subject to change without notice. For more information call us at 1-800-377-7655 (USA and Canada). Outside of North America call +1 (410) 358-3600.