

Superior Performance For The Installing Pro

The SCi Series has been developed specifically for the independent retailer, custom installer and integrator market.

- **They Share Cutout Sizes And Accessories** with TCi/LCi for maximum sales flexibility.
- **Follows TCi/LCi Cosmetics And Industrial Design** as a logical good/better/best strategy.
- **All New Drivers, Tweeters And Crossovers.**
- **Designed From The Ground Up As Our Best Entry Level Product.**
- **Same Weatherproof Hardware And Grilles As TCi**
- **Six Models:** two rectangular, four round, for virtually invisible placement in every conceivable location.
- **Dynamic Balance® Polymer Composite Drivers** for smooth widerange response with low distortion.
- **3/4" And 1" Silk Dome Tweeters** with neodymium magnets for clear, detailed highs.
- **Durable, Moisture Resistant Materials**, including Butyl Rubber surrounds, for safe use in kitchen, bath & sauna.
- **Paintable, Powder-coated Aluminum Grilles** allow SCi Series speakers to virtually disappear in your room!
- **Installation Is Easy As 1-2-3** with the Rotating Cam installation system.
- **Pre-Construction Brackets** (same brackets as TCi series SC60, SC80, SC65) are available for all models.



| Model | Shape | Driver Complement | Pre-Construction Bracket | Speaker/ Bracket Packing Measure |
|-------|--|--|----------------------------|----------------------------------|
| SC50 | Round 2-way Coaxial in-ceiling loudspeaker | 5 1/4" midwoofer driver 3/4" Aimable Silk Dome Tweeter | PB50, bracket for 50 | Each/Pair |
| SC60 | Round 2-way in-ceiling loudspeaker | 6 1/2" midwoofer driver 3/4" Aimable Silk Dome Tweeter | PB LC/TC60, Bracket for 60 | Each/Pair |
| SC80 | Round 2-way in-ceiling loudspeaker | 8" midwoofer driver 1" Aimable Silk Dome Tweeter | PB LC/TC80, Bracket for 80 | Each/Pair |
| SC65 | Rectangular 2-way in-wall loudspeaker | 6 1/2" midwoofer driver 3/4" Aimable Silk Dome Tweeter | PB LC/TC65, Bracket for 65 | Each/Pair |
| SC85 | Rectangular 2-way in-wall loudspeaker | 8" midwoofer driver 1" Aimable Silk Dome Tweeter | PB85, Bracket for SC/RC85 | Each/Pair |
| SC6s | Dual input 2-way in-ceiling loudspeaker | 6 1/2" dual voice coil midwoofer driver Two 3/4" Metallized Dome Tweeters | Fits RC60 cutout | Each |

| Model | Overall Freq Response | -3dB Limits | Recommended Amplification | Sensitivity | Nominal Impedance |
|-------|-----------------------|-------------|---------------------------|-------------|-------------------|
| SC50 | 50Hz-20kHz | 70Hz-20kHz | 20-100W | 88dB | 80hm |
| SC60 | 40Hz-20kHz | 60Hz-20kHz | 20-100W | 89dB | 80hm |
| SC80 | 35Hz-20kHz | 50Hz-20kHz | 20-100W | 90dB | 80hm |
| SC65 | 32Hz-20kHz | 60Hz-20kHz | 20-100W | 89dB | 80hm |
| SC85 | 30Hz-20kHz | 50Hz-20kHz | 20-100W | 90dB | 80hm |
| SC6s | 40Hz-20kHz | 55Hz-20kHz | 20-100W | 89dB | 80hm |

Specifications, dimensions and features subject to change without notice. For more information call us at 1-800-377-7655 (USA and Canada). Outside of North America call +1 (410) 358-3600.