









MARINE CERTIFIED





HIGH PERFORMANCE FACTORY UPGRADE

With its exceptional power handling, each speaker includes a three-quarter inch terylene tweeter for optimized mids and highs that blend perfectly with the gut-thumping lows from our polypropylene woofers. The tweeters have been re-engineered for zero protrusion, and the entire speaker has a reduced mounting depth for a precise, drop-in fit. We've also ensured the mounting holes correctly align with all vehicles for the easiest installation on the market today. Love your Polk speakers but still want your factory grille? Every DB Plus speaker includes a set of 3M adhesive stickers you can put just about anywhere in your vehicle to show off your Polk pride.











DB Plus Series Coaxial and Component Systems Specifications

	DB402	DB522	DB652	DB462	DB572	DB692	DB 5252	DB6502
Туре	4" coaxial	5.25" coaxial	6.5" coaxial	4" x 6" coaxial	5" x 7" coaxial	6" x 9" three-way	5.25" component	6.5" component
Driver Complement (inches & mm)	4" 101.60 mm	5.25" 133.35 mm	6.5" 165 mm	4" x 6" 101.6 mm x 152.4 mm	5" x 7" 127 mm x 177.8 mm	6" x 9" 152.4 mm x 228.6 mm	5.25" 133.35 mm	6.5" 165 mm
Tweeter Complement (inches & mm)	0.75" 19 mm	0.75" 19 mm	0.75" 19 mm	0.75" 19 mm	0.75" 19 mm	0.75" + 0.5" 19 mm + 13 mm	0.75" 19 mm	0.75" 19 mm
Cutout Dimensions (inches & mm)	4.09" 104 mm	4.76" 121 mm	5.0" 127 mm	4" x 6" 101.6 mm x 152.4 mm	4.92" x 7.15" 125 mm x 181.6 mm	5.97" x 8.80" 151.6 mm x 223.5 mm	4.76" 121 mm	5.0" 127 mm
Mounting Height (inches & mm)	0.22" 5.59 mm	0.31" 8 mm	0.47" 12 mm	0.18" 4.57 mm	0.51" 12.95 mm	0.66" 16.76 mm	0.28" 7.11 mm	0.41" 10.41 mm
Mounting Depth: Top (inches & mm)	1.79" 45.5 mm	1.74" 44.2 mm	1.77" 45 mm	1.81" 46 mm	2.24" 57 mm	3.25" 82.5 mm	1.74" 44.2 mm	1.77" 45 mm
Mounting Depth: Bottom (inches & mm)	2.00" 51 mm	2.01" 51.2 mm	2.12" 54 mm	1.91" 48.6 mm	2.76" 70 mm	3.83" 97.3 mm	2.02" 51.2 mm	2.23" 54 mm
Peak Power handling	135 W	300 W	300 W	150 W	225 W	450 W	300 W	300 W
Continuous Power Handling	45 W	100 W	100 W	50 W	75 W	150 W	100 W	100 W
Nominal Impedance (ohm)	4	4	4	4	4	4	4	4
Frequency Response (Hz)	60Hz- 22kHz	55Hz- 22kHz	40Hz-22kHz	50Hz- 22kHz	35Hz- 22kHz	30Hz- 22kHz	50Hz- 23kHz	35Hz-23kHz
Grille Height	14.07 mm	17.55 mm	20 mm	n/a	n/a	22.94 mm	17.55 mm	20 mm
Sensitivity (dB)	90	91	92	90	92	93	91	92
Crossover Characteristics	1st Order (Tweeter) at 4.5 kHz	1st Order (Woofer and Tweeter) at 4.5 kHz	1st Order (Woofer) 2nd Order (Tweeter) at 4.5 kHZ	1st Order (Tweeter Only) at 4.5 kHz	1st Order (Woofer and Tweeter) at 4.5 kHz	1st Order (Tweeter) 2nd Order (Midrange) at 4 kHz	2nd Order (Woofer and Tweeter) at 5.5 kHz	2nd Order (Woofer and Tweeter) at 5.5 kHz



EXPECT GREAT SOUND

Having built our reputation as "The Speaker Specialists" for more than 40 years, we take pride in our superior sound and build quality, which features many patented and award-winning audio innovations, like Dynamic Balance and VoiceAdjust technologies. For the people of Polk, building audio products is not just a job—it's a passion. And if you're going to remember one thing, remember this: We live by the truest principle of what audio should deliver—great sound at an affordable price for everyone!